

Sudah Terima Dari : RS MATA UNDAAN
Recived From

Banyaknya : Dua Puluh Tiga Juta Enam Ratus Delapan Puluh Empat Ribu Enam Ratus Dua Puluh Lima Rupiah
Amount

Untuk Pembayaran :Pembayaran Ke II 50% Pekerjaan Tambah Perbaikan System Hydrant Sprinkler (GEDUNG MEDIK SENTRAL)
For Payment

Rp. 23,684,625

Pembayaran dengan Chegue / Bilyet Giro / Transfer

Nama : ANDRI SETIAWAN AFRISAL
Nomor rekening :2140790535
Bank :BCA

surabaya. 22 juni 2022



ANDRI SETIAWAN AFRISAL

Kwitansi ini dianggap sah, apabila pembayaran dengan Bilyet Giro / Chengue tsb dapat diuangkan
This receipt will be cleared after Bilyet Giro / Chegue can cleared

SAFTY VALVE



TYPE	Control Valve
CODE	959-M964
BODY	Ductile iron
SIZE	4"
PRESSURE	16Bar
MEDIA	Water
TEMP	0-70°C
PRODUCTNO	001
M/YEAR	2021.10
PROOFER	05

Installation and adjustment

Installation
The main valve will be installed horizontally with bonnet up. Clean all the stuff in the pipe and install with the direction.

Adjustment

1. Close the upstream gate valve and open the downstream gate valve to release the pressure. When the downstream pressure reaches 0.1MPa, turn off the downstream gate valve.
2. Turn adjusting threwn on the piloted valve to above loosen position.
3. Open the upstream gate valve slowly until full open.
4. Tighten downward adjusting threwn on the piloted valve, the outlet pressure will increase step by step until the set value, then lock the thread.
5. If adjusted pressure surpasses the set point, it must readjust from the first step (adjust from low pressure to high pressure).

16 Jun 2022 11.34.06

